**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

IN RE: The application of Donald J. Briggs Jr.

## TITLE OF THE INVENTION

Magnetic Top For Ladders and Method of Construction Thereof

## CROSS REFERENCE TO RELATED APPLICATIONS

Not Applicable

## STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT

Not Applicable

## BACKGROUND OF THE INVENTION

1. Field of the invention

This invention relates magnetic supports for ladders and particularly to a magnetic top built into a ladder.

2. Description of the Prior Art

Ladders have been used for thousands of years. The folding stepladder is one of a long progression of developments for ladders over the past few hundred years. One of the developments involving folding stepladders is the use of a support shelf. The shelf is designed to fold for storage and can hold things such as small tools and paint cans. As useful as this shelf is, there are problems. There is nothing to hold items on the shelf. Thus tools and paint cans have been known to fall from these shelves, causing injury and damage.

Several devices have been developed to retain things being used on the shelf, and indeed for items kept on other parts of the ladder. Some of these devices are found in the following patents. In U. S. Patent 5,098,052, a magnetic support tray is disclosed. This tray is fastened to the support shelf on a ladder using bolts and wing nuts to make it removable. In Patent No. 4,826,059, a magnetic tool holder is shown that can be attached to a ladder. Patent No. 5,503,245 teaches a ladder that has a top with a webbed design that allows tools and other items to be held in the web. Patent No, 5,758,807 discloses a magnetic paddle that holds screws and the like. The paddle can be secured to a ladder if desired. U. S. Patent No. 6,443,260 teaches a tray that is attached to the top of a ladder using bolts or other fasteners. The tray extend forward of the ladder and has compartments that hold tools, fasteners and paint cans. Finally, Patent No. 6,587,022 discloses a magnetic wrap that can be secured to the top of a ladder using hook and loop fasteners.

While all of these devices help workers keep organized and hold items on a ladder, they are all designed to be portable. Moreover, some of them are cumbersome and bulky.

## BRIEF DESCRIPTION OF THE INVENTION

The instant invention overcomes these problems. It is a ladder that has a top portion that has numerous magnets attached or embedded into it. The magnets surround the sides of the ladder top as well as attached to the top plate. In this way, tools, fasteners, paint cans, or any other metal items can be secured quickly and safely

to the ladder top at any time. Moreover, because the device uses thin, magnetic strips, the ladder top is no bulkier than a normal ladder top. Finally, because of the construction, the ladder top is not covered by anything that impairs using the top in a normal way, such as sitting or standing on the top (although this is not a recommended practice, many workers routinely do this as part of their working habits). With this device, workers can fully utilize the ladder as if there was no magnetic holder attached.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of a ladder showing the invention in place.

Figure 2 is a bottom view of the ladder top showing the invention in place.

Figure 3 is a front view of the top portion of a ladder showing the invention.

Figure 4 is a side view of the top portion of a ladder showing the invention.

Figure 5 is a cross-section of the ladder top showing details of one construction method.

Figure 6 is a top view of a portion of a mold showing a quantity of magnetic power placed in the mold.

## DETAILED DESCRIPTION OF THE INVENTION

Referring now to fig. 1, a perspective view of the invention **1** is shown. The invention is a ladder top **2** that is attached to a stepladder **3**. The lower portion of the ladder **3** is a standard ladder base. It has steps and a folding mechanism like any stepladder. The difference is in the top. The top **2** of the instant invention is a body that has four sides **4** that extend downward from a top plate **5**. Typically, the top is

rectangular as shown; however, it can be made in other configurations. For the rectangular body shown, there are two long sides **4a** and two short sides **4b**.

Referring now to figure 2, the underside of the top plate **5** is shown. Here, two magnetic strips **6** are shown. There are many ways to form the magnetic strips. In one case, or for existing ladders, magnetic strips can be attached to the ladder top using adhesives, although this is not preferred except for pre-existing ladders.

Throughout this specification, the term "strip" includes rectangular, square, round, or any other shape. Moreover, the magnets can be made of flexible material, a ceramic material or any other material that can be attached or embedded into a ladder head as described above.

Figure 3 shows the front of the ladder top (one of the long sides **4a**. Figure 4 shows one of the sides **4b**. In both figures, magnetic strips **6** are shown attached to the sides **4a** and **4b**. Note that both the front and back as well as both sides of the ladder top have magnetic strips attached. This gives full coverage on the ladder and gives the user the greatest flexibility in positioning tools and equipment on the ladder top **5**.

Figure 5 is a cross-section of the preferred ladder top. In this embodiment, the magnetic strips are embedded in the actual material of the ladder top as part of the construction of the ladder top itself. In one form, the ladder top **5a** is formed of plastic or other materials. Magnetic strips **6** are then placed on the inner surfaces of the top and an epoxy coating **7** is then applied to the inner surface. This seals the magnetic strips in a solid coating that protects the magnetic strips and leaves them isolated from

contact. This also works to insulate the ladder top, which is a safety factor when the ladder is used around electrical equipment.

Another construction method forms the top as part of a molding process. In this construction, the magnetic strips are actually a magnetic powder that is mixed with the synthetic material used to form the ladder head, which is then poured into the mold. Figure 6 shows a portion of a mold **10**. The powder that is encased in plastic, resin, fiberglass or other materials common to the art using techniques that are well know in those arts is then molded as a single piece that acts as one magnet. By using the magnetic powder in this application manufacturing costs and time can be reduced. Once the molded top is finished, the "magnet" is permanently locked into the structure. Moreover, because they are completely encased, the ladder can be used around electric facilities without danger.

The molded ladder top then becomes a magnetic tool holder that can be used like a regular ladder without cumbersome devices attached to it. Moreover, the magnetic capabilities are automatic. There is no complicated apparatus to attach and remove. The ladder instantly receives and holds tool and other items safely and securely.

The present disclosure should not be construed in any limited sense other than that limited by the scope of the claims having regard to the teachings herein and the prior art being apparent with the preferred form of the invention disclosed herein and which reveals details of structure of a preferred form necessary for a better

understanding of the invention and may be subject to change by skilled persons within the scope of the invention without departing from the concept thereof.